



Techmo Asphalt-A2

Asphalt emulsion waterproofing

Description:

Waterproofing asphalt emulsion slurry consistency and high workability at room temperature.

Properties:

- It has high adhesion, forming an impermeable to dry.
- At room temperature dry in a few hours.
- Will not sag on vertical surfaces.
- Once dry is insoluble in water.

applications:

Very suitable and advantageous as primer on the cement-concrete surfaces prior to welding sheets asphalt. In decks, terraces, roofs, walls, medians, foundation, flooring, etc..

Presentation and Delivery:

Cans of 5 and 25 Kgs

Performance:

Depends on the porosity and surface roughness treat. Can be calculated as average of 500 to 750 grams. / M2 per hand.

Directions:

Surfaces to be treated should be clean and free of stains fats or oils.

Cold-applied, brush or roller. Do not apply wet weather or in temperatures below +5 ° C.

If several layers are applied must check that has dried the former before applying the next.

Storage and Preservation:

Keeping containers closed tightly conserved as at least 6 months.

Preserve the product from heat and frost.

NOTE:

The information and technical data given here are for guidance only and are subject to change without notice. They are based on data and knowledge considered to be true and accurate. However we have not control over the conditions under which our products are transported, stored, handled or used by our customers. by Therefore, our guarantee is limited exclusively to product quality. none information or recommendation interpreted to infringe any rule or legal provision.

Techmo Asphalt A-2: 1 of 1

