



# Techmodur Bonding Slurry

## Bridge adhesion to synthetic resins

### Description:

Bridge adhesion to synthetic resins, fillers mineral and organic and inorganic additives to promote anchoring cement based mortars and / or lime on or smooth concrete surfaces without surface absorption. Compound Acriloestirénica nature in aqueous medium, selected and silica binders. specially manufactured base to form a bridge between the mortar of plaster and concrete structural, improving adherence to those about them, avoiding descolgaduras.

### Fields of Application:

- Interior and exterior.
- Vertical and ceilings.

### Directions:

Mix 2 volumes Techmodur bonding slurry with 1 volume of water, mixed to achieve a homogeneous before application. Apply the product with roller or brush and apply the mortar has dried once Techmodur bonding slurry.

### And cautions:

The surface must be clean, free of dust, grease, oils, concrete release liquids.  
Do not apply when rain or frost.  
Do not apply at temperatures below 5 ° C or above 45 ° C.  
Clean with warm water the tools used, the Like the hands and the skin, immediately after use.  
Do not apply mortar Grout Techmodur monolayer Wet Adhesion.  
Not harmful nor gives off toxic fumes.

### Storage:

1 year in sealed original packaging.

### Presentation:

Lot of 23 Kg

### Important Note:

Do not apply the mortar after three days of applying Techmo bonding slurry.

FEATURE	SPECIFICATION
Specific gravity	1.3 to 1.5
Viscosity	thixotropic paste
Density (g / cc)	1.65 + / - 0.5 g / cc
Performance	0.3 kg/m2 (undiluted)
Thinner	water
Color	yellow ocher
Fire behavior	not flammable
Application of the mortar	From 4 to 6 hours
Finish	wrinkled

### NOTE:

The information and technical data given here are for guidance only and are subject to change without notice. They are based on data and knowledge considered to be true and accurate. However we have not control over the conditions under which our products are transported, stored, handled or used by our customers. by Therefore, our guarantee is limited exclusively to product quality. none information or recommendation interpreted to infringe any rule or legal provision.